

M

(12) **UK Patent Application** (19) **GB** (11) **2 166 058 A**

(43) Application published 30 Apr 1986

(21) Application No 8407267

(22) Date of filing 21 Mar 1984

(71) Applicant  
Christopher Bailes,  
73 Waverley Street, Stockton, Cleveland TS18 3JH

(72) Inventor  
Christopher Bailes

(74) Agent and/or Address for Service  
Christopher Bailes,  
73 Waverley Street, Stockton, Cleveland TS18 3JH

(51) INT CL<sup>4</sup>  
A63B 5/20


(52) Domestic classification  
A6M 9

(56) Documents cited  
GB A 2092013

(58) Field of search  
A6M  
Selected US specifications from IPC sub-class A63B


(54) **Skipping rope spinner**

(57) The spinner comprises a drilled steel bar having a further hole through its sides for passage and securing of the rope and is fastened to the handle by means of a screw as shown. When assembled, the rope will revolve on the screw.



GB 2 166 058 A




## POOR QUALITY



SHEET 2


2166058

12 DIA BAR



MATERIAL M.S.




ITEM ①




SECTION A-A

SHEET 3

2166058



MATERIAL M.S.



POOR QUALITY

## SPECIFICATION

### Skipping rope spinner

- 5 The only good skipping ropes revolve on the bearings and are costly to make.  
 Item (1) shows that my invention does away with the use of bearings.  
 Item (1) a steel bar is drilled with a 10 mm drill (internally) for  $\frac{3}{4}$  of its length. A 5 mm hole is then drilled through the other  $\frac{1}{4}$ . This 5 mm hole secures the whole spinner with a screw into the handle.  
 Item 1 shows a 10 mm hole drilled through the side of the spinner for the rope to go through to be secured on the outside.  
 When assembled the rope will revolve on the screw.

### 20 CLAIMS

1. I claim that this is the first Rope Spinner that is fixed with a screw (behind) the rope nearest the handle.  
 2. I also claim this is the first Rope Spinner that has the Rope attached through a hole in the side of the Spinner.

### CLAIMS

- Amendments to the claims have been filed, and have the following effect:—  
 Claims 1 and 2 above have been deleted or textually amended.  
 New or textually amended claims have been filed as follows:—
- 35 1. A skipping rope which retates at right angle to the user.  
 2. A skipping rope as claimed in claim 1 which has the minimum of friction between rope and handle.  
 40 3. A skipping rope as claimed in Claim 1 and Claim 2 which provides easy adjustment by the user of the length of rope.  
 4. A skipping rope as claimed in Claims 1, 2 and 3 which does not require the rope to be screwed to any rotating part.  
 45 5. A skipping rope comprising a swivel mounted on a screw and secured with a clamp to produce the effect declared in Claims 1, 2, 3 and 4.  
 50 6. A skipping rope as claimed in Claims 1, 2, 3, 4 and 5 which can be easily adjusted in length to meet the user's requirements.  
 7. A skipping rope comprising a length of solid flexible material and swivel at either end which is threaded through the outside of the corresponding end of the rope and secured with a clamp, which can be cut to any length and easily re-fitted by the user.  
 55 8. A skipping rope as claimed in Claim 5 where a swivel provided on each handle comprises a low friction rotating connection.  
 9. A skipping rope as claimed in any preceding claim whereby the rotating swivel is mounted on a handle by a threaded fastener  
 60 such as a screw taken through the swivel and

spacer and in to the end of the handle.

10. A skipping rope as claimed in Claim 8 wherein a metal clamp, in order to hold the rope in place, is clamped at each end of the rope.  
 70

11. A skipping rope substantially as hereinbefore described with reference to, and as shown in Fig. 1 of the accompanying drawing.

Printed in the United Kingdom for  
 Her Majesty's Stationery Office, Dd 8818935, 1986, 4235.  
 Published at The Patent Office, 25 Southampton Buildings,  
 London, WC2A 1AY, from which copies may be obtained.